



KEMFLEX SD

EXCEEDS EN 12115

APPLICATION :

- Superior design for use in chemical plants, ship, barge and tank truck service.
- Exceptional flexible chemical hose for suction and discharge applications for different types of acids, alkalis, salts and alcohols
- Braided construction has excellent flexibility and resistance to kinking
- Working pressure of 20bar / 300PSI for maximum safety
- Designed with fully conductive rubber compounds for added safety, ideal for applications in which static electricity can occur
- Classification Grade Ω/T

TEMPERATURE RANGE :

- -40 °F to 212 °F
 - -40 °C to 100 °C
- OPEN END STEAM CLEANING UP TO 266°F/130°C (MAX 30 MINUTES)

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE :

- Smooth and homogeneous
- Conductive, black ultra-high molecular weight polyethylene (UHMWPE)
- Electrical conductive R < 10⁶ Ω

REINFORCEMENTS :

- Multiple high tensile textile braids
- Dual steel helix wire

MATERIAL COVER :

- Black, smooth EPDM rubber
- Electrical conductive R < 10⁶ Ω
- Excellent abrasion, weather and ozone resistance

BRANDING:

- White and blue spiral stripe:
- GOODALL KEMFLEX SD • CHEMICAL EN 12115 20 BAR – 300 PSI Ω/T
- Embossed strip:
- GOODALL • KEMFLEX • EN 12115:2011 • UPE • SD • DN * • 20 BAR • 300 PSI • Ω/T •

STANDARD LENGTHS:

- 40 meters
- 131.2 feet

KEMFLEX SD

ID		OD		maximum working pressure		minimum burst pressure		vacuum	minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	%	mm	inch	kg/m	lb./ft.
13.0	1/2	23	0.91	20	300	80	1200	80	98	3.8	0.33	0.22
19.0	3/4	31	1.22	20	300	80	1200	80	125	4.9	0.58	0.39
25.0	1	37	1.46	20	300	80	1200	80	150	5.9	0.71	0.48
32.0	1 1/4	44	1.73	20	300	80	1200	80	175	6.9	0.86	0.58
38.0	1 1/2	51	2.01	20	300	80	1200	80	225	8.9	1.18	0.79
50.0	2	66	2.60	20	300	80	1200	80	275	10.8	1.90	1.28
75.0	3	91	3.58	20	300	80	1200	80	350	13.8	2.81	1.89
100.0	4	116	4.57	20	300	80	1200	80	675	26.6	3.59	2.41

All data at 68°F/20°C

Goodall KEMFLEX SD • CHEMICAL EN 12115 20 BAR - 300 PSI Ω/T



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.