



INFERNO

APPLICATION:

- Developed for use in construction, chemical and petroleum industries
- Greatest value when performance versus price
- Easy identification by its red cover and yellow mylar stripe
- Can also be used as a hot water transfer hose

TEMPERATURE RANGE:

- -40°F to +450°F
- -40°C to +232°C

BURST PRESSURE:

- Minimum 10:1

MATERIAL TUBE:

- Extruded, smooth proprietary chlorobutyl (CIIR) compound
- Excellent resistance to resist pop-corning and blistering

REINFORCEMENTS:

- Multiple braids of high tensile steel wire
- Braided with brass plated wire for corrosion resistance and improved adhesion

MATERIAL COVER:

- Red, smooth EPDM rubber
- Pin-pricked
- Excellent abrasion, weather and ozone resistance

BRANDING:

- Yellow spiral mylar stripe: GOODALL • INFERNO • STEAM 250 PSI 450°F
- Embossed stripe: N2711 • INFERNO • 250 PSI MAX WP • 450°F MAX TEMP • 10001 • * • CAUTION TIGHTEN CLAMPS BEFORE USING • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

- 100 feet, 30.5 meters

INFERNO

ID		OD		maximum working pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	mm	inch	kg/m	lb./ft.
12.7	½	25.7	1.01	17	250	63.5	2.5	0.61	0.41
19.0	¾	32.3	1.27	17	250	101.6	4.0	0.80	0.54
25.0	1	39.4	1.55	17	250	127.0	5.0	1.12	0.75
32.0	1 ¼	45.5	1.79	17	250	152.4	6.0	1.37	0.92
38.0	1 ½	51.8	2.04	17	250	177.8	7.0	1.61	1.08
51.0	2	67.3	2.65	17	250	254.0	10.0	2.56	1.72
63.0	2 ½	80.5	3.17	17	250	330.2	13.0	3.51	2.36
76.0	3	94.2	3.71	17	250	406.4	16.0	4.29	2.88

All data at 68° F / 20° C

Goodall INFERNO • STEAM 250 PSI 450° F



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.

