HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER:

Goodall Rubber Co. of Canada LP

| | Registered to ISO 9001:2008 Quality Management System | | |
|----------------|---|--|--|
| | (File number 000593) & ISO 14001:2004 Environmental | | |
| | Management System (File number 000593) | | |
| HOSE TYPE: | HOT TOMATO PASTE | | |
| SPECIFICATION: | N2523 | | |
| SIZE: | 3" | | |

HOSE DIMENSIONS

ID (inches): OD (inches): MINIMUM BEND RADIUS (inches): LENGTH (feet) AVAILABLE:

| 3" | |
|-------|--|
| 3.96" | |
| 17" | |
| 100' | |

HOSE DESIGN

| TUBE: | White Chlorobutyl | |
|----------------|---|--|
| REINFORCEMENT: | High Tensile Textile Braids | |
| COVER: | Black Neoprene | |
| STRIPE: | N/A | |
| BRANDING: | GOODALL® • N2523 • HOT TOMATO PASTE HOSE • 200 PSI MAX WP • | |
| | MADE IN CANADA 10001 • REFER TO INDUSTRY | |
| - | RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE • | |

SPECIFICATION

| MAXIMUM WP: | 200 PSI W.P. |
|--------------------|----------------|
| SAFETY RATIO: | 4:1 Minimum |
| TEMPERATURE RANGE: | -40°F to 275°F |

Notes:

Prepared By: Jason Whiteside

Released By: Laura Bishop

Issue Date: 04/07/2016

Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.

Contact your local Eriks or Lewis-Goetz Co division for any questions.