

Goodall[®] HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER: Goodall Rubber Co. of Canada LP
Registered to ISO 9001:2008 Quality Management System
(File number 000593) & ISO 14001:2004 Environmental
Management System (File number 000593)

HOSE TYPE: MINE POWER

SPECIFICATION: N2550

SIZE: 1/2" - 1"

HOSE DIMENSIONS

ID (inches):	1/2"	3/4"	1"
OD (inches):	1.01"	1.23"	1.49"
MINIMUM BEND RADIUS (inches):	3.75"	4"	5"
LENGTH (feet) AVAILABLE:	UP TO 250'		

HOSE DESIGN

TUBE: Oil Resistant Nitrile Blend

REINFORCEMENT: High Tensile Textile Braid

COVER: Red Abrasion Resistant SBR Blend

STRIPE: White

BRANDING: Goodall N2550 Mine Power Air/Water 400 PSI Max W.P.
Made in Canada 10001
Refer to Industry Recommendations for Proper Care & Maintenance

SPECIFICATION

MAXIMUM WP: 400 PSI W.P.

SAFETY RATIO: 4:1 Minimum

TEMPERATURE RANGE: -40°F to 180°F

Notes: _____

Prepared By: Jason Whiteside

Released By: Laura Bishop

Issue Date: 09/22/15

Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.

Contact your local Eriks or Lewis-Goetz Co division for any questions.