



HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER: Goodall Rubber Co. of Canada LP
 Registered to ISO 9001:2008 Quality Management System
 (File number 000593) & ISO 14001:2004 Environmental
 Management System (File number 000593)

HOSE TYPE: CGA TYPE 1 LPG HOSE

SPECIFICATION: N2567

SIZE: 3/4" - 2"

HOSE DIMENSIONS

ID (inches):	3/4"	1 1/2"	2"
OD (inches):	1.30"	2.18"	2.77"
MINIMUM BEND RADIUS (inches):	4"	7"	10"
LENGTH (feet) AVAILABLE:	100'		

HOSE DESIGN

TUBE: High Grade Black LPG Resistant Nitrile

REINFORCEMENT: High Tensile Stainless Steel & Textile Braid

COVER: Abrasion, Weather & Ozone Resistant Neoprene

STRIPE: Yellow & Blue Spiral

BRANDING: Goodall MH8393, RV L.P. Gas Hose Issue No. XXXXX C.G.A. Type 1 Max W.P.
 350 PSIG (2.4 Mpa) Quarter, Year 10001
 Refer to Industry Recommendations for Proper Care & Maintenance

SPECIFICATION

MAXIMUM WP: 350 PSI W.P.

SAFETY RATIO: 5:1 Minimum

TEMPERATURE RANGE: -40°F to 180°F

Notes: _____

Prepared By: Jason Whiteside

Released By: Andrew Bellamy

Issue Date: 12/6/2022

Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.

Contact your local Eriks division for any questions.