



# HOSE DATA SHEET

## GENERAL INFORMATION

**MANUFACTURER:** Goodall Rubber Co. of Canada LP  
 Registered to ISO 9001:2008 Quality Management System  
 (File number 000593) & ISO 14001:2004 Environmental  
 Management System (File number 000593)

**HOSE TYPE:** Air

**SPECIFICATION:** N2705

## HOSE DIMENSIONS

<b>ID (inches):</b>	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
<b>OD (inches):</b>	0.97	1.21	1.51	1.72	1.95	2.56	3.15	3.64	4.38
<b>Working Pressure (psi)</b>	400	400	400	400	400	400	400	400	300
<b>MINIMUM BEND RADIUS (inches):</b>	3.0	3.5	5.0	5.5	6.0	9.0	13.0	14.5	18.5
<b>WEIGHT (lbs) PER FT:</b>	0.29	0.37	0.49	0.61	0.82	1.09	1.47	1.78	3.01
<b>LENGTH (feet) AVAILABLE:</b>	100								

## HOSE DESIGN

**TUBE:** Extruded, Proprietary SBR

**REINFORCEMENT:** Multiple high tensile textile braids

**COVER:** Yellow, abrasion resistant SBR

**STRIPE:** BLACK

**BRANDING:** GOODALL N2705 ROCK BREAKER AIR  
 \* PSI MAX W.P. MADE IN CANADA 10001  
 REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE  
 & MAINTENANCE

## SPECIFICATION

**SAFETY RATIO:** 4:1 MINIMUM

**TEMPERATURE RANGE:** -40°F to 200°F

**Notes:** \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Prepared By:** Laura Bishop

**Released By:** Laura Bishop

**Issue Date:** 03/19/15

*Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.  
 Contact your local Eriks or Lewis-Goetz Co division for any questions.*