



HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER: Goodall Rubber Co. of Canada LP
 Registered to ISO 9001:2008 Quality Management System
 (File number 000593) & ISO 14001:2004 Environmental
 Management System (File number 000593)

HOSE TYPE: STEAM HOSE

SPECIFICATION: N2774

SIZE: 1/2", 3/4" AND 1"

HOSE DIMENSIONS

ID:	1/2"	3/4"	1"
OD:	1.16"	1.44"	1.63"
MINIMUM BEND RADIUS (IN):	3"	4"	5"
WEIGHT (LBS) PER FT:	0.46	0.63	0.74
LENGTH (FT) AVAILABLE:	100	100	100

HOSE DESIGN

TUBE: CHLOROBUTYL

REINFORCEMENT: MULTIPLE FIBREGLASS BRAIDS

COVER: WHITE EPDM

STRIPE: RED

BRANDING: GOODALL N2774 FIBREGLASS STEAM 250PSI MAX WP 450°F MAX
 TEMP CAUTION TIGHTEN CLAMPS BEFORE USING
 MADE IN CANADA 10001 REFER TO INDUSTRY
 RECOMMENDATIONS FOR PROPER CARE

SPECIFICATION

MAXIMUM WP: 250 PSI

SAFETY RATIO: 10:1 MINIMUM

TEMPERATURE RANGE: -40°F TO 450°F

Notes: _____

Prepared By: LAURA BISHOP
Approved By: LAURA BISHOP

Issue Date: 01/15/15

*Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.
 Contact your local Eriks or Lewis-Goetz Co division for any questions.*