



# HOSE DATA SHEET

## GENERAL INFORMATION

**MANUFACTURER:** Goodall Rubber Co. of Canada LP  
 Registered to ISO 9001:2008 Quality Management System  
 (File number 000593) & ISO 14001:2004 Environmental  
 Management System (File number 000593)

**HOSE TYPE:** SUPER MINE KING II

**SPECIFICATION:** N4000

**SIZE:** 3/4" - 2"

## HOSE DIMENSIONS

<b>ID (inches):</b>	3/4"	1 1/4"	2"
<b>OD (inches):</b>	1.36"	2.01"	2.96"
<b>MINIMUM BEND RADIUS (inches):</b>	3.5"	5"	10"
<b>LENGTH (feet) AVAILABLE:</b>	250'	100'	100'

## HOSE DESIGN

**TUBE:** Extruded, High Grade, Heat & Oil Resistant Proprietary Nitrile Blend

**REINFORCEMENT:** Multiple High Tensile Nylon Braids

**COVER:** Black Abrasion, Weather & Ozone Resistant SBR

**STRIPE:** Yellow & Green Spiral

**BRANDING:** Goodall N4000 Super Mine King II Air \* PSI W.P. Made in Canada 10001  
 Refer to Industry Recommendations for Proper Care & Maintenance

## SPECIFICATION

**MAXIMUM WP:** 3/4"-1 1/4" 550 PSI W.P. 2" 475 PSI W.P.

**SAFETY RATIO:** 4:1 Minimum

**TEMPERATURE RANGE:** -40°F to 200°F

**Notes:** \* Maximum W.P.

---



---



---

**Prepared By:** Jason Whiteside

**Released By:** Laura Bishop

**Issue Date:** 07/11/2016

*Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.*

*Contact your local Eriks or Lewis-Goetz Co division for any questions.*