



HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER: Goodall Rubber Co. of Canada LP
Registered to ISO 9001:2008 Quality Management System
(File number 000593) & ISO 14001:2004 Environmental
Management System (File number 000593)
HOSE TYPE: OXYGEN SCARFING HOSE
SPECIFICATION: N8139
SIZE: 3/8" - 3"

HOSE DIMENSIONS

| | | | | | | | | |
|--------------------------------------|------------|-------|-------|-------|--------|--------|-------|-------|
| ID (inches): | 3/8" | 1/2" | 3/4" | 1" | 1 1/4" | 1 1/2" | 2" | 3" |
| OD (inches): | .76" | 1.05" | 1.30" | 1.52" | 1.87" | 2.12" | 2.72" | 3.76" |
| MINIMUM BEND RADIUS (inches): | 2" | 2.5" | 3" | 4.5" | 5" | 6.5" | 11" | 15" |
| LENGTH (feet) AVAILABLE: | Up to 250' | | | | 100' | 100' | 100' | 100' |

HOSE DESIGN

TUBE: High Grade Neoprene
REINFORCEMENT: Multiple High Tensile Wire Braids
COVER: Black Chemical, Weather & Ozone Resistant Neoprene
STRIPE: N/A
BRANDING: Goodall N8139 Scarfing *PSI Max W.P. Made in Canada
Refer to Industry Recommendations for Proper Care & Maintenance

SPECIFICATION

MAXIMUM WP: 3/8" 2000 PSI W.P., 1/2" 1500 PSI W.P., 3/4" 1200 PSI W.P., 1" 1000 PSI W.P.,
1 1/4" 625 PSI W.P., 1 1/2" 500 PSI W.P., 2" 375 PSI W.P., 3" 375 PSI W.P.,
SAFETY RATIO: 4:1 Minimum
TEMPERATURE RANGE: -40°F to 180°F

Notes: * Maximum W.P.

Prepared By: Jason Whiteside

Released By: Laura Bishop

Issue Date: 15/03/2016

Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.

Contact your local Eriks or Lewis-Goetz Co division for any questions.