



## ACIDKEM SD

EXCEEDS EN 12115

### APPLICATION :

- Exceptional flexible chemical hose for suction and discharge applications for different types of acids, alkalis, esters and ketones
- Superior design for use in chemical plants, ship, barge and tank truck service.
- Braided construction has excellent flexibility and resistance to kinking
- Designed with fully conductive rubber compounds for added safety, ideal for applications in which static electricity can occur
- Ultra-high working pressure of 20bar/300 psi for more safety
- Classification Grade Ω/T

### TEMPERATURE RANGE :

- -40 °F to 203 °F
- -40 °C to 95 °C

OPEN END STEAM CLEANING UP TO 266°F/130°C (MAX 30 MINUTES)

### BURST PRESSURE:

- Minimum 4:1

### MATERIAL TUBE :

- Extruded, smooth, homogeneous and seamlessly black EPDM rubber
- Electrical conductive R < 10<sup>6</sup> Ω

### REINFORCEMENTS :

- Multiple high tensile textile braids
- Dual steel helix wire

### MATERIAL COVER :

- Black, smooth EPDM rubber
- Electrical conductive R < 10<sup>6</sup> Ω
- Very good abrasion, weather and ozone resistance

### BRANDING:

- Purple spiral stripe: GOODALL ACIDKEM SD • CHEMICAL EN 12115 20 BAR – 300 PSI Ω/T
- Embossed strip: GOODALL • ACIDKEM SD • EN 12115:2011 • EPDM • SD • DN\* • 20 BAR • 300 PSI • Ω/T • Month – Year

### STANDARD LENGTHS:

- 40 meters
- 131.2 feet

### ACIDKEM SD

ID		OD		maximum working pressure		minimum burst pressure		vacuum	minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	%	mm	inch	kg/m	lb./ft.
19.0	3/4	31	1.22	20	300	80	1200	92	125	4.9	0.60	0.40
25.0	1	37	1.46	20	300	80	1200	92	150	5.9	0.71	0.48
32.0	1 1/4	44	1.73	20	300	80	1200	92	175	6.9	0.88	0.59
38.0	1 1/2	51	2.01	20	300	80	1200	92	225	8.9	1.10	0.74
50.0	2	66	2.60	20	300	80	1200	92	275	10.8	1.90	1.28
63.0	2 1/2	79	3.11	20	300	80	1200	92	300	11.8	2.40	1.61
75.0	3	91	3.58	20	300	80	1200	92	350	13.8	3.08	2.07
100.0	4	116	4.57	20	300	80	1200	92	450	17.7	3.91	2.63

All data at 68°F/20°C

**Goodall** ACIDKEM SD • CHEMICAL EN 12115 20 BAR - 300 PSI Ω/T



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.