



DEFENDER

Medium Duty Air Hose

N1460

APPLICATION AND KEY POINTS:

- Medium-duty compressed air hose for use in construction sites
- Ideal for the transfer of high-temperature air
- May be used as a water transfer hose

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)/styrene-butadiene (SBR) blend
- Heat and oil-resistant

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Yellow styrene-butadiene (SBR)
- Excellent abrasion, weather, and ozone resistance
- Pin-pricked to resist cover blistering

BRANDING:

- Black longitudinal mylar stripe: GOODALL® N1460 DEFENDER • AIR ** PSI
- Embossed stripe: N1460 • DEFENDER • ** PSI MAX WP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

* Year - Month

** Maximum working pressure

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
2	2.58	550	9.0	1.59
3	3.59	400	14.5	2.50
4	4.68	400	18.5	3.71

All data at 68° F

LAYLINE:  **N1460 DEFENDER • AIR** 