



# VINTAGE

## Food Suction & Discharge Hose

### N2450

#### APPLICATION AND KEY POINTS:

- Flexible suction and discharge hose for use in wineries, breweries and other food and beverage industries
- Tasteless and odorless tube with high temperature resistance for open-end steam cleaning (max 30 minutes at 266° F)
- Extremely good bend radius
- Crush and kink-resistant design
- Meets FDA, 3A (18-03 CLASS 111) and USDA requirements

#### TEMPERATURE RANGE:

- -40°F to +230°F

#### BURST PRESSURE:

- Minimum 4:1

#### MATERIAL TUBE:

- White, smooth, seamless extruded chlorobutyl (CIIR)
- Non-contaminating formulation

#### REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual monofilament helix for added stability and flexibility

#### MATERIAL COVER:

- Grey EPDM
- Superior abrasion, weather, and ozone resistance

#### BRANDING:

- Blue longitudinal mylar stripe: GOODALL® N2450 VINTAGE • FOOD 250 PSI
- Embossed stripe: N2450 • VINTAGE • 250 PSI MAX WP • MEETS FDA, 3A 18-03 CLASS 111 & USDA REQS • 10001 • \* • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE

\* Year - Month

#### STANDARD LENGTHS:

- 100 feet

### TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
1	1.57	250	27	5.0	0.63
1 ½	2.09	250	27	6.5	0.92
2	2.63	250	27	8.5	1.25
3	3.76	250	27	16.0	2.23

All data at 68° F