

OXYGEN LANCE

N2527

APPLICATION AND KEY POINTS:

- Premium hose designed for lancing, purging and scarfing with hand-held equipment in the steel industry
- Used in steel mills and foundries

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded neoprene (CR)
- Oil-resistant

REINFORCEMENTS:

- Multiple high-tensile textile braids

MATERIAL COVER:

- Green styrene-butadiene (SBR)
- Exceptional abrasion, weather, and ozone resistance

BRANDING:

- Black spiral mylar stripe: GOODALL[®] N2527 OXYGEN LANCE • Oxygen ** PSI
- Embossed stripe: N2527 • OXYGEN LANCE • ** PSI MAX WP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

** Maximum Working Pressure

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1/2	1.06	500	2.0	0.41
3/4	1.33	500	2.5	0.57
1	1.54	500	3.0	0.66
2	2.56	300	12.0	1.0

All data at 68° F