



BLACK DRAGON

Crack Sealer Hose

N2533

APPLICATION AND KEY POINTS:

- Delivery hose for the transfer of hot tar and asphalt
- Ideal for use as a wand hose or crack sealer melter and applicator
- Extremely flexible and kink-resistant construction

TEMPERATURE RANGE:

- -40°F to +350°F (400°F intermittent)

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded neoprene (CR)
- High heat resistance

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Black neoprene (CR)
- Superior heat and oil resistance
- Excellent weather and ozone resistance

BRANDING:

- Red spiral mylar stripe: GOODALL® N2533 BLACK DRAGON • CRACK SEALER 300PSI
- Embossed stripe: N2533 • BLACK DRAGON CRACK SEALER SERVICE ONLY • 300 PSI Max WP • 10001 •
- * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
3/4	1.19	300	3.0	0.50
1	1.55	300	4.0	0.86

All data at 68° F

LAYLINE:  **N2533 BLACK DRAGON • CRACK SEALER**  