



BLACK DEVIL

Hot Tar & Asphalt Hose

N2586

APPLICATION AND KEY POINTS:

- Suction and discharge hose for the transfer of hot tar and asphalt
- A highly reliable transfer hose between trucks, rail cars or storage tanks
- Full vacuum rating

TEMPERATURE RANGE:

- -40°F to +350°F (400°F intermittent)

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Exceptional heat and oil resistance

REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual steel helix wire for added stability and flexibility

MATERIAL COVER:

- Black neoprene (CR)
- Excellent abrasion, weather, and ozone resistance
- Moderate resistance to oils and fuels

BRANDING:

- Red longitudinal mylar stripe: GOODALL® N2586 BLACK DEVIL • TAR & ASPHALT 150 PSI
- Embossed stripe: BLACK DEVIL • TAR & ASPHALT SERVICE • 150 PSI MAX WP • 350F MAX TEMP • 400F INTERMITTENT • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
3	3.79	150	28	11.5	2.23

All data at 68° F