

# **GREEN PAPERMILL** Washdown Hose N2644

# **APPLICATION AND KEY POINTS:**

- Medium-duty wash down hose for paper mills
- Extremely flexible and kink-resistant
- Available in assembly lengths with an innovative built on nozzle that eliminates the danger of scratching sensitive screens and machinery, and prevents leaks at the nozzle junction
- The nozzle directs a steady water supply pattern that saves time in washdown

### **TEMPERATURE RANGE:**

-40°F to +180°F

# **BURST PRESSURE:**

Minimum 4:1

## **MATERIAL TUBE:**

- Smooth, seamless extruded styrene-butadiene (SBR)
- Abrasion-resistant

### **REINFORCEMENTS:**

• Multiple high-tensile textile braids

### **MATERIAL COVER:**

- Green styrene-butadiene (SBR)
- Exceptional abrasion, weather, and ozone resistance

#### **BRANDING:**

- White spiral mylar stripe: GOODALL<sup>®</sup> N2644 GREEN PAPERMILL WATER 300 PSI
- Embossed stripe: N2644 GREEN PAPERMILL 300 PSI MAX WP • \* • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

\* Year - Month

# **STANDARD LENGTHS:**

- 100 feet for bulk hose
- \*\* 1 ¼" size is not available in bulk lengths
- See table for hose with nozzle length

| TECHNICAL SPECIFICATIONS |         |              |             |                |                             |
|--------------------------|---------|--------------|-------------|----------------|-----------------------------|
| ID (in)                  | OD (in) | Max WP (psi) | Min BR (in) | Weight (lb/ft) | Hose With<br>Nozzle Lengths |
| 3/4                      | 1.25    | 300          | 3.5         | 0.41           | 50'                         |
| 1                        | 1.47    | 300          | 4.5         | 0.54           | 50′<br>100′                 |
| 1 <sup>1</sup> /4**      | 1.72    | 300          | 6.5         | 0.56           | 50'                         |
| 2                        | 2.53    | 300          | 10.0        | 1.00           | N/A                         |
| All data at 68° F        |         |              |             |                |                             |

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES. EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance, and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental, and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.