

ARCTIC TUFF

Low Temp Fuel Discharge Hose

N2698

APPLICATION AND KEY POINTS:

- Discharge hose for the transfer of petroleum-based products such as gasoline, oil, diesel and other petroleum product
- Constructed for in-plant use or tank truck
- May be used on a reel
- Flexibility maintained in extreme cold temperatures

TEMPERATURE RANGE:

- -65°F to +190°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Designed to withstand extreme cold temperatures

REINFORCEMENTS:

- Multiple high-tensile textile braids
- Anti-static wire

MATERIAL COVER:

- Blue neoprene (CR)
- Vibrant blue color for high visibility
- Excellent resistance to weather, ozone, and petroleum based products
- Designed to withstand extreme cold temperatures

BRANDING:

- Red longitudinal mylar stripe: GOODALL[®] N2698 ARCTIC TUFF • PETROLEUM 200 PSI
- Embossed stripe: N2698 • ARCTIC TUFF -65°F TO +190°F TEMP • 200 PSI MAX WP • * • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

| ID (in) | OD (in) | Max WP (psi) | Min BR (in) | Weight (lb/ft) |
|---------|---------|--------------|-------------|----------------|
| 3/4 | 1.25 | 200 | 4.0 | 0.42 |
| 1 | 1.52 | 200 | 5.0 | 0.56 |
| 1 1/4 | 1.74 | 200 | 6.0 | 0.63 |
| 1 1/2 | 2.05 | 200 | 7.0 | 0.86 |

All data at 68° F