



# NUTRALON SD GREY

## Food Suction & Discharge Hose

### N2708

#### APPLICATION AND KEY POINTS:

- Food suction and discharge hose for transfer of milk products, animal fat, vegetable oil, fruit juices, and other food products
- Suitable for alcohol 96% at 104°F (intermittent at 208°F - 30 minutes)
- For tank truck or in-plant service
- Braided construction has excellent flexibility and resistance to kinking
- Improved ergonomics for operators
- Complies with multiple international regulations including 3A (18.3 CLASSII), USDA, FDA, BFR and EC 1935/2004
- Easy to clean because of the smooth tube
- ADI (Animal Derived Ingredient) Free
- Phthalate-free
- Non-marking abrasion-resistant cover

#### TEMPERATURE RANGE:

- -22°F to 212°F
- Open end steam cleaning up to 266°F (max 20 minutes)

#### BURST PRESSURE:

- Minimum 4:1

#### MATERIAL TUBE:

- White, smooth, seamless extruded nitrile (NBR)
- Non-contaminating formulation

- Complies to the most stringent international food regulations
- Excellent resistance to fatty foods like animal fats and vegetable oils
- Does not propagate bacteria growth
- Excellent resistance to the most common cleaning agents

#### REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual steel helix wire for added stability and flexibility

#### MATERIAL COVER:

- Grey neoprene (CR)
- Superior abrasion, weather, and ozone resistance
- Resistant to vegetable oils and animal fats
- Non-marking

#### BRANDING:

- White and red spiral mylar stripe: GOODALL® N2708 NUTRALON SD • FOOD 10 BAR – 150 PSI
- Embossed stripe: NUTRALON SD • DN \* • 10 BAR-150 PSI • MEETS FDA, BFR, EC 1935/2004, 3A 18-03 CLASS II & USDA REQS • MFR C-Y-M • MADE IN CANADA 10001

\* DN size

#### STANDARD LENGTHS:

- 100 feet

#### TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
1	1.46	150	27	6.0	0.57
1 ½	2.01	150	27	8.0	0.83
2	2.60	150	27	9.0	1.50
3	3.58	150	27	13.0	2.42

All data at 68° F

**LAYLINE:**  **N2708 NUTRALON SD • FOOD**  

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance, and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental, and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.