



THERMOFLEX RED

Steam Hose

N2712

APPLICATION AND KEY POINTS:

- Economical choice for use in harsh oilfield environments and general steam/boiler service

TEMPERATURE RANGE:

- -40°F to +450°F

BURST PRESSURE:

- Minimum 10:1

MATERIAL TUBE:

- Smooth, seamless extruded EPDM
- Specifically formulated for steam applications

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Red EPDM
- Excellent abrasion, weather, and ozone resistance
- Pin-pricked to resist cover blistering

BRANDING:

- Embossed stripe: Goodall® • THERMOFLEX • STEAM
- 250 PSI MAX WP • 450°F MAX TEMP • MFR C-Y-M •
- MADE IN CANADA 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE

STANDARD LENGTHS:

- 1/2, 3/4 and 1 inch: 50 feet
- 2 inch: 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1/2	1.01	250	3	0.38
3/4	1.27	250	4	0.49
1	1.57	250	5	0.70
2	2.59	250	10	1.69

All data at 68° F