



CO₂ KING

Discharge Hose

N2716

APPLICATION AND KEY POINTS:

- Premium hose for low-temperature transfer of CO₂ from truck to bulk storage tank
- Specialty compounds designed for low-temperature service

TEMPERATURE RANGE:

- -65°F to +180°F

BURST PRESSURE:

- Minimum 5:1

MATERIAL TUBE:

- Smooth, seamless extruded neoprene (CR)
- Formulated for low temperature service
- Has FDA-compliant materials

REINFORCEMENTS:

- Multiple high-tensile stainless steel wire braids
- Stainless steel wires provide excellent corrosion resistance

MATERIAL COVER:

- Black neoprene (CR)
- Abrasion, weather, and ozone resistant
- Pin-pricked to resist cover blistering

BRANDING:

- Green spiral mylar stripe: GOODALL® N2716 CO₂ KING • SS • CO₂ 450 PSI
- Embossed stripe: N2716 • CO2 KING • SS • 450 PSI MAX WP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1	1.55	450	3.0	0.87
1 ½	2.08	450	4.75	1.30
2	2.58	450	6.5	1.80

All data at 68° F

LAYLINE:  **N2716 CO2 KING • SS • CO2**   