



BLACK DIAMOND

CSA Type 2 LPG Hose N2737

APPLICATION AND KEY POINTS:

- Hard-wearing transfer hose for LPG
- Compatible with propane, butane, and natural gas for use in well-ventilated areas
- ATTENTION! Not to exceed 20 psi max working pressure when used for natural gas transfer
- Superior strength, durability and kink resistance created by the combination of high-tensile polycotton and stainless steel braids
- Meets CSA 8.1:15 (Type II)
- Approved to UL 21 specifications

TEMPERATURE RANGE:

- -40°F to +200°F

BURST PRESSURE:

- Minimum 5:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG


REINFORCEMENTS:

- Multiple high-tensile stainless steel wire braids
- Stainless steel wires provide excellent corrosion resistance
- Single high-tensile polycotton braid

MATERIAL COVER:

- Black neoprene-impregnated polycotton braid
- Excellent weather, ozone, petroleum, and oil resistance

BRANDING:

- White longitudinal mylar stripe: GOODALL® N2737 BLACK DIAMOND • CGA TYPE II 350 PSI (2.4 MPa)
- #Q## • 10001 • MH8393 LP GAS HOSE ISSUE NO. E7734  US C***US REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1 ³ / ₃₂	0.77	350	4.0	0.26
5/8	1.10	350	6.5	0.31
7/8	1.22	350	7.0	0.40
1 1/8	1.50	350	8.0	0.65
1 1 ³ / ₁₆	2.25	350	15.0	0.83

All data at 68° F