



# BLACK DIAMOND

## CSA Type 2 LPG Hose N2737

### APPLICATION AND KEY POINTS:

- Hard-wearing transfer hose for LPG
- Compatible with propane, butane, and natural gas when assembled in compliance with local, regional, and national codes and standards. For use only in well-ventilated areas
- Superior strength, durability and kink resistance created by the combination of high-tensile polycotton and stainless steel braids
- Meets CSA 8.1:15 (Type II)
- Approved to UL 21 specifications

### TEMPERATURE RANGE:

- -40°F to +200°F

### BURST PRESSURE:

- Minimum 5:1

### MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG


### REINFORCEMENTS:

- Multiple high-tensile stainless steel wire braids
- Stainless steel wires provide excellent corrosion resistance
- Single high-tensile polycotton braid

### MATERIAL COVER:

- Black neoprene-impregnated polycotton braid
- Excellent weather, ozone, petroleum, and oil resistance

### BRANDING:

- White longitudinal mylar stripe: GOODALL® N2737 BLACK DIAMOND • CGA TYPE II 350 PSI (2.4 MPa)
- #Q## • 10001 • MH8393 LP GAS HOSE ISSUE NO. E7734  C\*\*\*US REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

### STANDARD LENGTHS:

- 100 feet

### TECHNICAL SPECIFICATIONS

| ID (in) | OD (in) | Max WP (psi) | Min BR (in) | Weight (lb/ft) |
|---------|---------|--------------|-------------|----------------|
| 13/32   | 0.77    | 350          | 4.0         | 0.26           |
| 5/8     | 1.10    | 350          | 6.5         | 0.31           |
| 7/8     | 1.22    | 350          | 7.0         | 0.40           |
| 1 1/8   | 1.50    | 350          | 8.0         | 0.65           |
| 1 13/16 | 2.25    | 350          | 15.0        | 0.83           |

All data at 68° F

**LAYLINE:**  **N2737 BLACK DIAMOND • CGA TYPE II**  

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance, and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental, and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.