

# ELEPHANT HIDE PLUS

## LPG Hose N2805

### APPLICATION AND KEY POINTS:

- Superior LPG transfer hose for demanding conditions
- Compatible with propane, butane, and natural gas for use in well-ventilated areas
- ATTENTION! Not to exceed 20 psi max working pressure when used for natural gas transfer
- Reinforced with corrosion-resistant stainless steel braids
- Exceptional high abrasion-resistant cover
- Ideal for tank truck service and trailer-to-storage use
- Approved to UL 21 specifications

### TEMPERATURE RANGE:

- -40°F to +180°F

### BURST PRESSURE:

- Minimum 5:1

### MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG


### REINFORCEMENTS:

- Multiple high-tensile stainless steel wire braids
- Stainless steel wires provide excellent corrosion resistance
- Single high-tensile textile braid

### MATERIAL COVER:

- Black neoprene (CR)
- Superior abrasion resistance
- Formulated to resist cracking from exposure to weather and ozone conditions
- Pin-pricked to resist cover blistering

### BRANDING:

- Yellow, black and blue spiral mylar stripe: GOODALL® N2805 ELEPHANT HIDE PLUS • LPG 350 PSI
- Embossed stripe: N2805 • ELEPHANT HIDE PLUS • MH8393 •  • LP GAS HOSE ISSUE NO E8073 • \* • 350 PSI (2.4 Mpa) MAX WP • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

\* Year - Month

### STANDARD LENGTHS:

- 100 feet

## TECHNICAL SPECIFICATIONS

| ID (in) | OD (in) | Max WP (psi) | Min BR (in) | Weight (lb/ft) |
|---------|---------|--------------|-------------|----------------|
| 1       | 1.62    | 350          | 4.0         | 0.88           |
| 1 ¼     | 1.87    | 350          | 6.0         | 1.05           |
| 1 ½     | 2.12    | 350          | 7.5         | 1.25           |
| 2       | 2.70    | 350          | 9.0         | 1.85           |
| 3       | 3.88    | 350          | 18.0        | 3.50           |

All data at 68° F