

# **ELEPHANT HIDE PLUS** LPG Hose N2805

## **APPLICATION AND KEY POINTS:**

- Superior LPG transfer hose for demanding conditions
- Reinforced with corrosion resistant stainless steel
  braids
- Exceptional high abrasion resistant cover
- Ideal for tank truck service and trailer to storage use
- Approved to UL 21 specifications

## **TEMPERATURE RANGE:**

-40°F to +180°F

#### **BURST PRESSURE:**

Minimum 5:1

## **MATERIAL TUBE:**

- Smooth, seamless extruded Nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG

#### **REINFORCEMENTS:**

- Multiple high-tensile Stainless-steel wire braids
- Stainless-steel wires provide excellent corrosion resistance
- Single high-tensile textile braid

## MATERIAL COVER:

- Black Neoprene (CR)
- Superior abrasion resistance
- Formulated to resist cracking from exposure to weather and ozone conditions
- Pin-pricked

#### **BRANDING:**

- Yellow, black and blue spiral mylar stripe: GOODALL<sup>®</sup> N2805 ELEPHANT HIDE PLUS
   LPG 350 PSI
- Embossed stripe: N2805 ELEPHANT HIDE PLUS MH8393 • N • LP GAS HOSE ISSUE NO E8073 • \* • 350 PSI (2.4 Mpa) MAX WP • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

\* Year - Month

#### **STANDARD LENGTHS:**

• 100 feet

TECHNICAL SPECIFICATIONS				
ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1	1.62	350	4.0	0.88
1 1/4	1.87	350	6.0	1.05
1 1/2	2.12	350	7.5	1.25
2	2.70	350	9.0	1.85
3	3.88	350	18.0	3.50
All data at 68° F				

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES. EXPRESSED OR IMPLIED. INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures tor selection. installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising trom tart claims (including without limitation negligence and strict liability) or other theories of law.