



SUPER DRAGON

Hydrocarbon Drain Hose N2820

APPLICATION AND KEY POINTS:

- To drain hydrocarbons from the operation of steam cleaning vessels, tanks, and piping systems in the chemical and petrochemical industry
- Superior core that is crush and kink-resistant

TEMPERATURE RANGE:

- -40°F to +250°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Exceptional heat and oil resistance

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion
- Textile breaker yarn results in higher adhesion levels.

MATERIAL COVER:

- Blue Hypalon (CSM)
- Abrasion, oil, weather, and ozone-resistant
- Excellent resistance to petroleum products and the effects of weathering
- Superior color-stay properties

BRANDING:

- White spiral mylar stripe: GOODALL® N2820 SUPER DRAGON • HYDROCARBON DRAIN 500 PSI
- Embossed stripe: N2820 • SUPER DRAGON • HYDROCARBON DRAIN • 500 PSI MAX WP • * • 10001
- REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- 3/4 inch and 1 inch: 50 feet
- 2 inch: 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
3/4	1.26	500	2.5	0.54
1	1.57	500	3.0	0.77
2	2.63	500	10.0	1.65

All data at 68° F

LAYLINE:  **N2820 SUPER DRAGON • HYDROCARBON DRAIN**  