



# SUPER DRAGON

## Hydrocarbon Drain Hose N2820

### APPLICATION AND KEY POINTS:

- To drain hydrocarbons from the operation of steam cleaning vessels, tanks, and piping systems in the chemical and petrochemical industry
- Superior core that is crush and kink-resistant

### TEMPERATURE RANGE:

- -40°F to +250°F (350°F intermittent)

### BURST PRESSURE:

- Minimum 5:1

### MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Exceptional heat and oil resistance

### REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion
- Textile breaker yarn results in higher adhesion levels.

### MATERIAL COVER:

- Blue Hypalon (CSM)
- Abrasion, oil, weather, and ozone-resistant
- Excellent resistance to petroleum products and the effects of weathering
- Superior color-stay properties

### BRANDING:

- White spiral mylar stripe: GOODALL® N2820 SUPER DRAGON • HYDROCARBON DRAIN 500 PSI
- Embossed stripe: N2820 • SUPER DRAGON • HYDROCARBON DRAIN • 500 PSI MAX WP • \* • 10001
- REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

\* Year - Month

### STANDARD LENGTHS:

- 3/4 inch and 1 inch: 50 feet
- 2 inch: 100 feet

### TECHNICAL SPECIFICATIONS

| ID (in) | OD (in) | Max WP (psi) | Min BR (in) | Weight (lb/ft) |
|---------|---------|--------------|-------------|----------------|
| 3/4     | 1.26    | 500          | 2.5         | 0.54           |
| 1       | 1.57    | 500          | 3.0         | 0.77           |
| 2       | 2.63    | 500          | 10.0        | 1.65           |

All data at 68° F

**LAYLINE:**  **N2820 SUPER DRAGON • HYDROCARBON DRAIN**  