



SUPER INFERNO

Steam Hose

N2861

APPLICATION AND KEY POINTS:

- High-pressure steam hose for saturated steam at 450°F
- Heavy-duty construction with a 20:1 burst pressure for increased user safety
- Longer service life and reduced downtime
- The best choice for steam when safety and performance are valued

TEMPERATURE RANGE:

- -40°F to +450°F

BURST PRESSURE:

- Minimum 20:1

MATERIAL TUBE:

- Smooth, seamless extruded chlorobutyl (CIIR)
- Excellent resistance to popcorning and blistering

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Red EPDM
- Excellent abrasion, weather, and ozone resistance
- Pin-pricked to resist cover blistering

BRANDING:

- Black spiral mylar stripe: GOODALL® N2861 SUPER INFERNO • STEAM 250 PSI 450°F
- Embossed stripe: N2861 SUPER INFERNO 450°F MAX TEMP 250 PSI MAX WP • CAUTION TIGHTEN CLAMPS BEFORE USING • * • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE •

* Year - Month

STANDARD LENGTHS:

- 50 feet

TECHNICAL SPECIFICATIONS

| ID (in) | OD (in) | Max WP (psi) | Min BR (in) | Weight (lb/ft) |
|---------|---------|--------------|-------------|----------------|
| 3/4 | 1.27 | 250 | 4.0 | 0.60 |
| 1 | 1.55 | 250 | 5.0 | 0.89 |

All data at 68° F