



THERMOFLEX BLACK

Steam Hose

N2918

APPLICATION AND KEY POINTS:

- Developed specifically for use in petrochemical and chemical refineries
- Can also be used as a hot water transfer hose
- High-pressure steam hose for saturated steam at 450°F

TEMPERATURE RANGE:

- -40°F to +450°F

BURST PRESSURE:

- Minimum 10:1

MATERIAL TUBE:

- Smooth, seamless extruded EPDM
- Specifically formulated for steam applications

REINFORCEMENTS:

- Multiple high-tensile zinc-plated steel wire braids
- Zinc-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Black EPDM
- Excellent abrasion, weather, and ozone resistance
- Pin-pricked to resist cover blistering

BRANDING:

- Embossed stripe: GOODALL® THERMOFLEX • 250 PSI MAX WP • 450°F MAX TEMP • MFR C-Y-M • MADE IN CANADA 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE

STANDARD LENGTHS:

- 1/2, 3/4 and 1 inch: 50 feet
- 2 and 3 inch: 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1/2	1.01	250	3.0	0.42
3/4	1.26	250	4.0	0.46
1	1.55	250	5.0	0.68
2	2.74	250	10.0	1.77
3	3.71	250	16.0	2.68

All data at 68° F