



NITROGEN

N2928

APPLICATION AND KEY POINTS:

- For use in nitrogen service to purge lines in refineries, petrochemical, and general industries.
- Designed with fully conductive rubber compounds for added safety
- Classification Grade Ω /T

TEMPERATURE RANGE:

- -40°F to +176°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded EPDM
- Electrically conductive $R < 10^6\Omega$

REINFORCEMENTS:

- Single high-tensile textile braid

MATERIAL COVER:

- Yellow & Black spiral EPDM
- Abrasion, weather, and ozone resistant
- Electrically conductive $R < 10^6\Omega$
- Pin-pricked to resist cover blistering

BRANDING:

- Embossed stripe: GOODALL® • EN 12115 • NITROGEN
- DN * • 24 BAR • 4:1 MIN BP • 350 PSI • Ω /T • MFR C-Y-M • MADE IN CANADA 10001 •

* DN size

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1/2	0.91	350	3.5	0.26
3/4	1.25	350	4.9	0.34
1	1.43	350	5.9	0.38

All data at 68° F