



SUPER HARDROK II

Heavy Duty Air & Water Mine Hose N3000

APPLICATION AND KEY POINTS:

- Heavy-duty and high-pressure compressed air hose for use in mines, quarries and construction jobs
- Special heavy-duty construction with superior flexibility and kink resistance
- Excellent in bull air line service
- Ideal for the safe transfer of high-temperature air
- May also be used as a very robust oil transfer hose

TEMPERATURE RANGE:

- -40°F to +268°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Exceptional heat and oil resistance

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Yellow styrene-butadiene (SBR)
- Excellent abrasion, weather, and ozone resistance
- Pin-pricked to resist cover blistering

BRANDING:

- Black spiral mylar stripe: GOODALL® N3000 SUPER HARDROK II • AIR 900 PSI
- Embossed stripe: N3000 • SUPER HARDROK II • 900 PSI MAX WP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
2	2.77	900	8.0	2.15

All data at 68° F

LAYLINE:  **N3000 SUPER HARDROK II • AIR**  