



OILFIELD CHEMICAL TRANSFER BLACK

APPLICATION :

- Hose for transfer of aggressive chemicals to hydraulic fracturing blenders in pressure, gravity flow and/ or suction service.
- The hose is available in several colored covers, to prevent cross contamination on site.
- Can be open end steam cleaned up to 50 psi (3,5 bar) at 212°F (100°C)

TEMPERATURE RANGE :

- -40°F to 250°F
- -40°C to 121°C

BURST PRESSURE:

- 4:1

MATERIAL TUBE :

- Modified cross-linked Polyethylene (Mod. XLPE)
- Beige

REINFORCEMENTS :

- Spiral-plyed synthetic fabric with steel wire helix

MATERIAL COVER :

- Black abrasion, weather, and ozone resistant EPDM
- Corrugated

BRANDING:

- White lazy spiral mylar stripe: GOODALL OILFIELD CHEMICAL TRANSFER . MODIFIED XLPE 200 PSI
- Embossed stripe : GOODALL OILFIELD CHEMICAL TRANSFER 200 PSI (13,8 bar) -40 to 250°F (-40 to +121°C) MAX TEMP

STANDARD LENGTHS:

- 200 feet
- 61 meters

OILFIELD CHEMICAL TRANSFER BLACK

ID		OD		maximum working pressure		minimum burst pressure		vacuum HG	minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	%	mm	inch	kg/m	lb./ft.
25,4	1"	37,22	1,47	13,8	200	55,2	800	92	102	4	0,77	0,51
32	1 1/4"	42,37	1,67	13,8	200	55,2	800	92	127	5	0,82	0,55
38	1 1/2"	48,77	1,92	13,8	200	55,2	800	92	127	5	0,99	0,66
50,8	2"	61,87	2,44	13,8	200	55,2	800	92	178	7	1,33	0,89
63,5	2 1/2"	76,19	3	13,8	200	55,2	800	92	204	8	1,95	1,31
76	3"	89,18	3,51	13,8	200	55,2	800	92	254	10	2,37	1,59
102	4"	114,48	4,5	13,8	200	55,2	800	92	356	14	3,06	2,06

All data at 68°F/20°C

Goodall OILFIELD CHEMICAL TRANSFER • MODIFIED XLPE 200PSI

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.

