

WORK OVER RIG

Air & Oil Transfer Discharge Hose N1253

APPLICATION AND KEY POINTS:

- Air & oil transfer discharge
- Heavy-duty construction

TEMPERATURE RANGE:

- -40°F to +180°F For Oil Service
- -40°F to +268°F For Air Service Only

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded neoprene (CR)
- Oil-resistant

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Black neoprene (CR)
- Excellent abrasion, weather, and ozone resistance
- Moderate resistance to oils and fuels

BRANDING:

- Yellow longitudinal mylar stripe
- Embossed stripe: GOODALL® N1253 RIG LIQUID SERVICE 2000 PSI MAX W.P. • AIR/GAS SERVICE 1000 PSI MAX W.P. • C-*** • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE

*** Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Mini BR (in)	Weight (lb/ft)
2	2.74	1000	9.5	2.77
2 ½	3.37	1000	10.5	3.38
3	3.86	1000	15	3.84

All data at 68° F

* Maximum Working Pressure refers to use with Air/Gas and increases to 2000 PSI for liquid