

PETROFLO

Petroleum Transfer Hose N2490

APPLICATION AND KEY POINTS:

- Petroleum transfer hose used in tank truck and in-plant service to transfer oil and other petroleum base products
- Hose construction gives excellent bending radius

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Excellent oil resistance

REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual steel helix wire for added stability

MATERIAL COVER:

- Tan Hypalon (CSM)
- Abrasion, oil, weather, and ozone-resistant

BRANDING:

- Double green spiral mylar stripe
- Embossed stripe: GOODALL[®] N2490 PETROFLO PETROLEUM 150 PSI MAX W.P. MADE IN CANADA 10001 •*• REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
2	2.57	150	27	7	1.17
2½	3.13	150	27	9	1.52
3	3.66	150	27	10	2.03

All data at 68° F