

LPG

CSA Type 1 LPG Hose N2567

APPLICATION AND KEY POINTS:

- For conveying LPG from bulk to tank truck and from truck to domestic storage
- Compatible with propane, butane, and natural gas for use in well-ventilated areas
- Meets CSA 8.1:15 (Type 1)
- Approved to UL 21 specifications

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 5:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG


REINFORCEMENTS:

- Multiple high-tensile stainless steel wire braids
- Stainless steel wires provide excellent corrosion resistance
- Single high-tensile textile braid

MATERIAL COVER:

- Black neoprene (CR)
- Abrasion, weather, and ozone resistant
- Pin-pricked to resist cover blistering

BRANDING:

- Yellow, Black & Blue spiral mylar stripe
- Embossed stripe: GOODALL[®] MH8393 N2567,  L.P. GAS HOSE ISSUE NO XXXXX C.G.A. TYPE 1 MAX W.P. 350 PSIG (2.4 MPa) QUARTER, YEAR 10001 REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1 ½	2.18	350	7	1.32
2	2.70	350	10	1.93

All data at 68° F