



PAPERMILL

Washdown Hose with Nozzle N2593

APPLICATION AND KEY POINTS:

- Medium-duty wash down hose for paper mills
- Extremely flexible and kink-resistant
- Non-marking cover
- Only available in 50 foot assemblies with built on nozzle
- Innovative built on nozzle eliminates the danger of scratching sensitive screens and machinery, and prevents leaks at the nozzle junction
- The nozzle directs a steady water spray pattern that saves time in washdown

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded styrene-butadiene (SBR)
- Abrasion-resistant

REINFORCEMENTS:

- Multiple high-tensile textile braids

MATERIAL COVER:

- Black styrene-butadiene (SBR)
- Excellent abrasion, weather, and ozone resistance
- Non-marking

BRANDING:

- White spiral mylar stripe
- Embossed stripe: GOODALL® N2593 PAPERMILL WASHDOWN 300 PSI MAX WP • MFR C-Y-M • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE MADE IN CANADA 10001

STANDARD LENGTHS:

- 50 foot assemblies with built on nozzle

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1	1.47	300	5	0.50
1 ¼	1.72	300	6	0.52

All data at 68° F