



SULFUR DIOXIDE

Discharge Hose (Wet)

N2683

APPLICATION AND KEY POINTS:

- Specifically designed for sulfur dioxide wet service 100% concentration

TEMPERATURE RANGE:

- 40°F to +180°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded EPDM
- High heat resistance
- Low permeation

REINFORCEMENTS:

- Multiple high-tensile stainless steel wire braids
- Stainless steel wires provide excellent corrosion resistance
- Single high-tensile textile braid

MATERIAL COVER:

- Black EPDM
- Abrasion, weather, and ozone resistant

BRANDING:

- Embossed stripe: GOODALL® N2683 SULFUR DIOXIDE SERVICE ONLY SS WIRE 250 PSI W.P. TO BE INSPECTED PRIOR TO EACH USE MFR C*** MADE IN CANADA 10001

*** Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

| ID (in) | OD (in) | Max WP (psi) | Min BR (in) | Weight (lb/ft) |
|---------|---------|--------------|-------------|----------------|
| 1 | 1.52 | 250 | 5 | 0.68 |
| 1 ½ | 2.12 | 250 | 7 | 1.18 |
| 2 | 2.73 | 250 | 9 | 1.78 |

All data at 68° F