

SUPER MINE KING II

Heavy Duty Air & Water Mine Hose N4000

APPLICATION AND KEY POINTS:

- Air & water general purpose
- Heavy-duty construction
- Kink resistant

TEMPERATURE RANGE:

- -40°F to +200°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Exceptional heat and oil resistance

REINFORCEMENTS:

- Multiple high-tensile textile braids

MATERIAL COVER:

- Black styrene-butadiene (SBR)
- Excellent abrasion, weather, and ozone resistance

BRANDING:

- Yellow & Green spiral mylar stripe
- Embossed stripe: GOODALL® N4000 • SUPER MINE KING II AIR • * PSI MAX WP • MFR C-Y-M • MADE IN CANADA 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE •

* Maximum working pressure

STANDARD LENGTHS:

- 100 feet
- See table for hose with nozzle length

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)	Hose with Nozzle Lengths
3/4	1.36	550	3.5	0.52	
1 1/4	2.01	550	7	0.79	
2	2.96	475	10	2.04	25'

All data at 68° F