INTELLIGENT HOSE TECHNOLOGY



SUPER MINE KING II Heavy Duty Air & Water Mine Hose N4000

APPLICATION AND KEY POINTS:

- Air & water general purpose
- Heavy-duty construction
- Kink resistant

TEMPERATURE RANGE:

-40°F to +200°F

BURST PRESSURE:

• Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Exceptional heat and oil resistance

REINFORCEMENTS:

• Multiple high-tensile textile braids

MATERIAL COVER:

- Black styrene-butadiene (SBR)
- Excellent abrasion, weather, and ozone resistance

BRANDING:

- Yellow & Green spiral mylar stripe
- Embossed stripe: GOODALL® N4000 SUPER MINE KING II AIR • * PSI MAX WP • MFR C-Y-M • MADE IN CANADA 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE •

* Maximum working pressure

STANDARD LENGTHS:

- 100 feet
- See table for hose with nozzle length

TECHNICAL SPECIFICATIONS					
ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)	Hose with Nozzle Lengths
3/4	1.36	550	3.5	0.52	
11/4	2.01	550	7	0.79	
2	2.96	475	10	2.04	25′
All data at 68° F					

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES. EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance, and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental, and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.