



# HOSE DATA SHEET

## GENERAL INFORMATION

**MANUFACTURER:** Goodall Rubber Co. of Canada LP  
 Registered to ISO 9001:2008 Quality Management System  
 (File number 000593) & ISO 14001:2004 Environmental  
 Management System (File number 000593)

**HOSE TYPE:** FLEXTUBE DRY CEMENT HOSE

**SPECIFICATION:** N2496

**SIZE:** 4"

## HOSE DIMENSIONS

<b>ID (inches):</b>	4"	
<b>OD (inches):</b>	4.44"	
<b>MINIMUM BEND RADIUS (inches):</b>	7'	
<b>LENGTH (feet) AVAILABLE:</b>	100	

## HOSE DESIGN

**TUBE:** High-Grade Abrasion Resistant and Static Conductive SBR/NR

**REINFORCEMENT:** Single High Tensile Textile Braid

**COVER:** Black Abrasion, Weather & Ozone Resistant SBR

**STRIPE:** N/A

**BRANDING:** Goodall N2496 Flexitube Dry Cement 100 PSI Max W.P.  
 Made in Canada 10001  
 Refer to Industry Recommendations for Proper Care & Maintenance

## SPECIFICATION

**MAXIMUM WP:** 150 PSI W.P.

**SAFETY RATIO:** 4:1 Minimum

**TEMPERATURE RANGE:** -20°F to 180°F

**Notes:** \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Prepared By:** Jason Whiteside

**Released By:** Laura Bishop

**Issue Date:** 06/06/2017

*Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.*

*Contact your local Eriks or Lewis-Goetz Co division for any questions.*