



HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER:	Goodall Rubber Co. of Canada LP
	Registered to ISO 9001:2008 Quality Management System
	(File number 000593) & ISO 14001:2004 Environmental Management System (File number 000593)
HOSE TYPE:	HYDROGEN CYANIDE
SPECIFICATION:	N2524
SIZE:	2"

HOSE DIMENSIONS

ID (inches):	2"
OD (inches):	2.88"±0.093"
MINIMUM BEND RADIUS (inches):	10"
LENGTH (feet) AVAILABLE:	100'

HOSE DESIGN

TUBE:	Extruded, high grade, HCN resistant proprietary CSM
REINFORCEMENT:	Two, high tensile, 304 stainless steel wire strands & dual steel helix wire
COVER:	Yellow, weather & ozone resistant high visibility, 3/32" thick CSM
STRIPE:	Red Spiral
BRANDING:	Goodall N2524 Hydrogen Cyanide 125 PSIG Max W.P. 188 PSIG Test
	Made in Canada 10001
	Refer to Industry Recommendations for Proper Care & Maintenance

SPECIFICATION

MAXIMUM WP:	125 PSI W.P.
SAFETY RATIO:	10:1 Minimum
TEMPERATURE RANGE:	-40°F to 180°F

Notes: _____

Prepared By: Jason Whiteside

Released By: LAURA BISHOP

Issue Date: 11/03/2016

Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.

Contact your local Eriks or Lewis-Goetz Co division for any questions.