



# HOSE DATA SHEET

## GENERAL INFORMATION

**MANUFACTURER:** Goodall Rubber Co. of Canada LP  
 Registered to ISO 9001:2008 Quality Management System  
 (File number 000593) & ISO 14001:2004 Environmental  
 Management System (File number 000593)

**HOSE TYPE:** SULFUR DIOXIDE DISCHARGE HOSE (WET)

**SPECIFICATION:** N2683

**SIZE:** 1/2" - 2"

## HOSE DIMENSIONS

<b>ID (inches):</b>	1/2"	3/4"	1"	1 1/2"	2"
<b>OD (inches):</b>	.96"	1.21"	1.52"	2.12"	2.73"
<b>MINIMUM BEND RADIUS (inches):</b>	3"	4"	5"	7"	9"
<b>LENGTH (feet) AVAILABLE:</b>	Up to 500 "		100'	100'	100'

## HOSE DESIGN

**TUBE:** EDPM

**REINFORCEMENT:** High Tensile Stainless Steel Wire & Textile Braid

**COVER:** Black EPDM

**STRIPE:** N/A

**BRANDING:** Goodall Spec N2683 Sulfur Dioxide Service Only Stainless Steel Wire -  
 250 PSI W.P. - To Prevent Serious Injury Hose Should be Inspected Prior to Use  
 Made in Canada 10001

## SPECIFICATION

**MAXIMUM WP:** 250 PSI W.P.

**SAFETY RATIO:** 4:1 Minimum

**TEMPERATURE RANGE:** -40°F to 180°F

**Notes:** \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Prepared By:** Jason Whiteside

**Released By:** 

**Issue Date:** 10/06/16

*Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.*

*Contact your local Eriks or Lewis-Goetz Co division for any questions.*