



HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER: Goodall Rubber Co. of Canada LP
 Registered to ISO 9001:2008 Quality Management System
 (File number 000593) & ISO 14001:2004 Environmental
 Management System (File number 000593)

HOSE TYPE: WARM WATER HOSE

SPECIFICATION: N2910

SIZE: 1 1/2"

HOSE DIMENSIONS

ID (inches):	1 1/2"	
OD (inches):	1.99"	
MINIMUM BEND RADIUS (inches):	7"	
LENGTH (feet) AVAILABLE:	100'	

HOSE DESIGN

TUBE: Extruded, EPDM

REINFORCEMENT: Multiple High Tensile Wire Braids

COVER: Green Abrasion Resistant EPDM

STRIPE: N/A

BRANDING: Goodall® N2910 250 PSI Max W.P. 200°F Max Temp Water Service
 Made in Canada 10001 Refer to Industry Recommendations for Proper Care &
 Maintenance

SPECIFICATION

MAXIMUM WP: 250 PSI W.P.

SAFETY RATIO: 4:1 Minimum

TEMPERATURE RANGE: -40°F to 200°F

Notes: _____

Prepared By: Jason Whiteside

Released By: _____

Issue Date: _____

Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.

Contact your local Eriks or Lewis-Goetz Co division for any questions.