



BLACK DIAMOND

CGA Type 2 LPG Hose

N2737

APPLICATION AND KEY POINTS:

- Hard-wearing transfer hose for LPG, propane, butane and natural gas
- Superior strength, durability and kink resistance created by the combination of high-tensile poly-cotton and stainless steel braids
- The Goodall Black Diamond hose is approved according to CAN/CGA-8.1-M86 (Type II) and UL

TEMPERATURE RANGE:

- -40°F to +200°F

BURST PRESSURE:

- Minimum 5:1

MATERIAL TUBE:

- Smooth, seamless extruded Nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG


REINFORCEMENTS:

- Multiple high-tensile Stainless-steel wire braids
- Stainless-steel wires provide excellent corrosion resistance
- Single high-tensile Poly-cotton braid

MATERIAL COVER:

- Black Neoprene impregnated Poly-cotton braid
- Excellent weather, ozone, petroleum, and oil resistance

BRANDING:

- White longitudinal mylar stripe: GOODALL® N2737 BLACK DIAMOND • CGA TYPE II 350 PSI (2.4 MPa)
- #Q## • 10001 • MH8393 LP GAS HOSE ISSUE NO. E7734  US C***US REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1 ³ / ₃₂	0.77	350	4.0	0.26
5/8	1.10	350	6.5	0.31
7/8	1.22	350	7.0	0.40
1 1/8	1.50	350	8.0	0.65
1 1 ³ / ₁₆	2.25	350	15.0	0.83

All data at 68° F